



As the number of users and the amount of data grows, how to find a storage which can offer complete data protection, good performance, with reliability and high scalability is the key for all enterprises and companies. The NetServ XS 12 Bay based on latest priNAS 6.0 operating system. Except for basic NAS functions, it supports a variety of advanced storage management and application features such as VAAI, Thin-Provisioning, etc, and it can be deployed easily in any IT environment since it supports multiple interfaces for different host server and clients.

For data protection, NetServ XS 12 Bay supports RAID level 0, 1, 5, 6, 10 and 50 mode, and drives can be set hot spares, have automatically hot rebuilding and online capacity expansion within the enclosure. NetServ XS 12 Bay has a fully-featured backup solution including manual or scheduled backup for file, folder, and shares, and it can be backup and restore from multiple local or remote devices. And there are volume clone, snapshot, remote replication, and data copy for options, which are all designed to ensure and enhance your precious data.

Features

- Account Manager support NIS
- Allows online capacity expansion within the enclosure
- Android/iOS mobile APP for monitoring
- Backup to Cloud (Amazon S3)
- Backup/Restore from attached storage (USB/eSATA/iSCSI/RDX/USM)
- Backup/Restore from remote share (CIFS/NFS)
- Bonjour Protocol, easily connect to NAS
- Compression (Support on ZFS file system)
- Central data and storage management
- Data backup via backup plan/schedule
- Data copy (1:1)
- Deduplication (Support on ZFS file system)
- EXT4 support extend over 16TB
- iSCSI/share volume replication
- ISO mount
- Latest volume snapshot technology
- Local and external account management, support large account import
- Online expansion file system
- Plug-in management
- Select share or file for backup/restore
- Share management and permission (support ACL setting)
- Support Internet Gateway
- Support iSCSI target for IP SAN
- Support iSCSI initiator
- Support iSCSI multi host
- Support e-mail notification, SNMP Trap/MIB and system log
- System configuration backup/restore
- Thin Provisioning
- Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS/ZFS)
- Volume replication to enhance data protection
- VMware ESXi 5 iSCSI/NFS VAAI support
- Wizard-oriented GUI design
- WORM (Write Once Read Many) support CIFS/NFS

Your Storage Solutions Partner

Detail features : 800-433-5133 , 978-455-9488 www.primearraystorage.com



Series Technical Specifications

NetServ XS 12 Bay

NAS Hardware Specification

Intel Pentium Dual Core 3.2GHz CPU or above
 Cache memory : 8GB DDR3 up to 16GB
 Four USB3.0 and Two USB2.0 ports
 Two Gigabit Ethernet ports
 Up to Twelve 2.5"/3.5" hot-swappable 6Gb/s SATA hard drives
 Real-time drive activity and status indicators
 Environmental monitoring unit
 Two(2) 400W hot-swappable power supplies with PFC

Environmental

Operating temp : 10°C~40°C(50°F~104°F)
 Relative humidity : 10%~85% Non-condensing

RAID Controller

Highpoint RocketRAID 2720
 Support RAID level: RAID 0, 1, 5, 6, 10, 50
 Support drive hot spare and automatic hot rebuild
 Allow online capacity expansion within the enclosure
 Locally audible event notification alarm

Physical Dimension

88(H) x 482(W) x 500(D)mm

Power requirements

AC 100V ~ 240V Full range
 8A ~ 4A, 47~63Hz

NAS Functionality

Storage Management

Volume management (Support ZFS, XFS, EXT3 and EXT4 file system)
 Support Compression and Deduplication (Support on ZFS file system)
 Disk usage statistics
 Hot spare drives
 iSCSI Target manager: Support LUN Mapping/Initiator Filter/Thin Provisioning
 VAAI support for iSCSI/NFS

General

Independent file server
 Multiple language support
 Support UPS
 Support LV encryption

System Management

Automatic IP address configuration
 Web browser-based management
 SNMP management and notification
 Fail-free online firmware upgrade
 Unicode support
 Multi-node management GUI
 System configuration backup/restore
 Central management
 Quick wizard
 APP for Android/iOS monitoring

Networking

Support NIC/Trunking/Load Balance/Fail Over/802.3ad
 DHCP Server/DHCP Client
 WINS Server
 Internet gateway
 DDNS

Protocols

TCP/IP, SMB/CIFS, NFS, SNMP, FTP/SFTP/FXP, HTTP, HTTPS, Telnet, SSH, AFP, WebDAV, Bonjour, TFTP

Client Operating Systems Support

Microsoft® Windows® 98/ME/NT/2000/XP/2003/Vista/2008/Win7/Windows 2012/Win 8
 Unix/Linux
 Mac OS

Authentication

Local user account/group
 Microsoft NT Domain Controller (PDC)

Microsoft Active Directory Authentication (ADS)

Network Information Service (NIS)

Support OpenLDAP service

Support creating users by batch

User quota management

Share level security

File level security

User ID security for NFS

Recycle bin (Samba)

File access log, audit (Samba)

Write Once Read Many (WORM)

Block Storage

iSCSI Target Support

Thin Provisioning support

VMware VAAI support

Virtualization

VMware/Citrix/Hyper-V

VMware VAAI for NFS support

Attached Storage

ISO Mount

USB/eSATA*/iSCSI initiator

Data Backup / Restore

Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS/ZFS)

Symantec BackupExec Agent (by additional installation)

Scheduling multi-snapshot (Support iSCSI snapshot)

Replication (Remote realtime data mirroring)

Scheduling Rsync Replication

Support NetVault backup client (by additional installation)

Support CA ARCserve (by additional installation)

Data copy (copy files to other share/attached storage)

Scheduling backup

Differential/incremental backup

iSCSI Replication

Amazon S3 backup

backup/restore from attached storage

(USB/eSATA*/iSCSI/RDX*/USM*)

Support Apple Time Machine

Plug-in management

Anti-Virus

Central management

iTunes Server

Virtualization (VM on NAS)

* By OEM request

Specification are subject to change without notice. All company and product names are trademarks of their respective owners.

Your Storage Solutions Partner

Detail features : 800-433-5133 , 978-455-9488 www.primearraystorage.com

